### DS-GA 1007 | Lecture 2

### Programming for Data Science

Jeremy Curuksu, PhD NYU Center for Data Science jeremy.cur@nyu.edu

February 10, 2023

### **DS-GA 1007 Curriculum**

#### **Programming for Data Science:**

- ► Introduction to Programming in Python
- Best Practice Programming and Software Engineering
- Program Efficiency
- Interacting with Programs
- Array Manipulation for Scientific Computing
- Data Visualization
- ► Advanced Data Objects (×4)
- Environments for Collaborative Programming
- ► Industrial Applications

# **Programming in Python**

**Best Practice** 

### **Best Practice Programming in Python**

#### **Last week:**

- What is programming?
- Primitive Data Types and Control Flow
- Compound Data Types: Tuples, Lists, Dictionaries

### **Today:**

- Modularization and Abstraction
- Functions and Objects in Python
- Testing and Debugging Programs

**Modularization and** 

**Abstraction** 

### **Programming Best Practices**

- Measured by amount of functionality, not volume
- ► **Modularization:** Decompose code in self-contained modules to keep code organized and coherent
- ► Abstraction: Define modules as functions or objects which can be reused. Leverage preexisting modules, either built-in or imported (NumPy, Pandas, ...)
- Document each module (input, output, properties)
- ► Test and debug modules individually, pre-emptively

**Functions in Python** 

### **Decomposition with Functions**

- Decompose to create structure: Functions should be self-contained and reusable
- ▶ Abstract to suppress details: Function should come with specifications or docstrings. A function can then be used as a black box: no need to see details
- Functions are not run until they are invoked
- ► Functions have:
  - A name
  - A body
  - A docstring (optional)
  - Input parameters (optional)
  - Returns outputs (optional)

### **Decomposition with Functions**

```
Function

def <function name>(<parameters>):
    """ DocString """
    <body>
    return <output>
```

#### **Example:**

```
def testeven(i):
    """ Input: A positive integer number
        Output: True if number is even, False if odd
    """
    print("Executing test even for i = {}".format(i))
    return i%2 == 0
```

### **Scope of Variables in Functions**

➤ **Scope:** A new "local" scope for variable names is created when the program enters a function

#### ► Local Scope:

- Variables defined inside a function are not defined outside the function
- Values fetched to function parameters get bound to local variable names when the function is invoked

#### Global Scope:

- Variables defined outside can be accessed inside ("visible everywhere")
- Variables defined outside cannot be modified inside

```
def f(x):
   """Return square of a number"""
   x = x**2
   return x
y = 10
f(y)
print(y)
               Output: ?
```

```
def f(x):
   """Return square of a number"""
   x = x**2
   return x
y = 10
f(y)
print(y)
               Output: 10
```

```
def f(x):
   """Return square of a number"""
   x = x**2
   return x
x = 10
f(x)
print(x)
               Output: ?
```

```
def f(x):
   """Return square of a number"""
   x = x**2
   return x
x = 10
f(x)
print(x)
              Output: 10
```

```
def f(x):
   """Return square of a number"""
   x = x**2
   return x
x = 10
x = f(10)
print(x)
              Output: 100
```

```
def f(x):
   """Return square of a number"""
   x = x**2
   return x
x = 10
x = f(x)
print(x)
              Output: 100
```

```
def f(x):
   x = x**2
   X = X + Y
   return x
y = 10
x = f(10)
print('x = {}, y = {}'.format(x,y))
Output: X = 110, y = 10
```

DS-GA 1007 | Lecture 2

```
def f(x):
   """Return square of a number"""
   y = x**2
   return y
y = 10
x = f(10)
print('x = {}, y = {}'.format(x,y))
Output: X = 100, y = 10
```

DS-GA 1007 | Lecture 2

```
def f(x):
   x = x**2 + y
   \Lambda = X
   return y
y = 10
x = f(10)
print('x = {}, y = {}'.format(x,y))
```

#### **Output:** UnboundLocalError

### **Input and Ouput to Functions**

#### **Input: parameters**

- Optional, from 0 to 256
- Can be any data type fit to operations happening inside the function
- Can be other functions
- Can be value or existing global variable name
- Global variables input as parameters get reassigned to local variable names

#### **Output: return or print**

- Optional
- Can use only 1 return with only 1 value per function, but can be any data type
- Can use as many print statements as desired
- ► If no return given, Python returns the value *None*
- Global variables are not impacted inside functions

**Objects in Python** 

### **Decomposition with Objects**

#### What are Objects?

- Objects are data abstraction. An object is a collection of:
  - ▶ Data Attributes: Internal representation of the object (equivalent to data variables)
  - Methods: Interface for interacting with the object (equivalent to functions)
- ► Objects are instances of a class
  - Class statements are blueprint to create objects
  - Once an object is created, its attributes and methods are accessed by the dot operator: objectname.attributename()

### **Decomposition with Objects**

```
Object

class name(<superclass>):
    """ DocString """
    <body>
```

#### **Example:**

#### **Define new type of object:**

```
class dog(animal):
    speed = 30
    race = 'Not specified'
    domesticated = True
```

#### Use the object:

```
fido = dog() # Create instance
print(fido.domesticated)
fido.speed = 20
fido.race = 'Schnauzer'
fido.cuteness = 'XXL'
```

## **Object Oriented Programming (OOP)**

#### **Advantages of OOP for Data Science**

- Create new types (=classes) of data objects
  - Create your own data types with custom attributes
  - Bundle together objects of common attributes
- ► Modularization => Divid & Conquer code development
  - Implement and test behavior of each class separately
  - Access attributes and methods consistently using the dot operator: No collision on variable and function names
- ► Abstraction => Easy to reuse code
  - Separate implementation of defining vs. using an object
  - ► Inheritance: Build layers of object abstractions that inherit behaviors from other classes of objects

### **Object Oriented Programming (OOP)**

#### Animal





### **Attributes and Methods of Objects**

#### Attributes and Methods are accessed by the "." operator

- ▶ Data Attributes
  - Data objects that make up the class
  - "What it is"

**Example:** Class 2Dcoordinate made up of two numbers

- ► **Methods** (Procedural Attributes)
  - Functions that only work with this class
  - "What it does"

**Example:** Class *2Dcoordinate* with a method to compute the distance between two *2Dcoordinate* objects

### **Methods of Object**

#### **Defining and Invoking Methods**

- When creating a method, the first argument passed to it (called self) must be the object itself
- Invoke the method with "." and Python automatically fills in self
- Other than self and ".", methods behave exactly like functions

#### **Define new type of object:**

```
class coordinate(object):
    x = 0.1
    y = 0.1
    def distance(self,other):
        dx2 = (x-other.x)**2
        dy2 = (y-other.y)**2
        return (dx2 + dy2)**0.5
```

#### Use the object:

```
p1 = coordinate()
p2 = coordinate()
p1.x = 0.8
p1.y = 0.2
d = p1.distance(p2)
print('Distance: ',d)
```

### The Object Initialization Method

#### The <u>\_ init</u>\_ Method

- ► A special method called \_\_init\_\_ can be created to initialize data attributes when creating an instance of the class
- Python automatically calls \_\_init\_\_ when creating an object
- Out of scope for this course: Implement set and get methods to access all data attributes of an object

#### Define new type of object:

```
class coordinate(object):
    def __init__(self,a,b):
        self.x = a
        self.y = b
```

#### Use the object:

```
p1 = coordinate(0.8,0.2)
p2 = coordinate(0.5,0.5)
d = p1.distance(p2)
print('Distance: ',d)
```

### **Example of New Data Object**

```
class coordinate(object):
   def __init__(self,a=0.1,b=0.1):
      self.x = a
      self.y = b
   def distance(self, other):
      dx2 = (self.x-other.x)**2
      dy2 = (self.y-other.y)**2
      return (dx2 + dy2)**0.5
p1 = coordinate(0.8, 0.2)
p2 = coordinate(0.5, 0.5)
d = p1.distance(p2)
print('Distance: ',d)
                  DS-GA 1007 | Lecture 2
```

### **Inheritance of Object Types**

- ► Parent class = Superclass
  - In Python all classes derive from a superclass



### **Inheritance of Object Types**

- ▶ Parent class = Superclass
  - In Python all classes derive from the parent class Object
- Child class = Subclass
  - Inherits all data and behaviors from parent class
  - Add more information and more behavior
  - Override behavior

    Sentient
    Being

    Animal

    Robot


    Plant

    Dog

    Cat

### **Inheritance of Object Types**

- ► For any data object in Python, you have access to methods in current class definition and up the hierarchy
- You can only use the first method up the hierarchy with that method name: A class may have method with same name as in superclass, but it overrides inherited method with same name



**Testing and Debugging** 

**Programs** 

### **Testing and Debugging Programs**

#### **▶** Defensive Programming:

- Modularization: Break up programs into modules (functions, objects) and leverage pre-existing modules
- ► **Abstraction**: Document specification for each module (expected input-output, assumptions on code design)

#### ► Test and debug modules individually:

- ► **Test**: Identify where and when errors happen
- Debug: Understand and solve errors
- Pre-emptively... Implement handles to raise exceptions and assert module specifications

### **Testing Programs**

#### **Testing** = **Identifying** where and when errors happen

- What to test?
  - ▶ **Unit test**: Test/validate each piece of program separately
  - Regression test: Add test for bugs as you find them
  - ► Integration test: Ensure overall program runs
- How to test?
  - Intuitive or Random test: Explore possible inputs and test cases randomly or based on intuition
  - ▶ Black Box test: Explore test cases through specification
  - ► Glass Box test: Explore test cases through code

### **Black Box Testing**

#### Design test cases without looking at code

- Only use specification to define typical values and edge cases
- Can be reused if implementation changes
- Can be done by someone other than the implementer

#### **Example: How would you test this function?**

```
def topgrade(1):
    '''Read list of grades and return highest one'''
    top = 1[0]
    for r in 1[1:]:
        if r > top: top = r
    return top
```

DS-GA 1007 | Lecture 2

## **Glass Box Testing**

#### Design test cases based on the code

- ▶ Use code to test all possible branchings, loops, etc
- ► A program is called *path-complete* if every potential scenario through code has been tested at least once
- Can run loops arbitrarily many times yet miss key scenarios

#### **Example: How would you test this function?**

```
def topgrade(1):
    '''Read list of grades and return highest one'''
    top = 1[0]
    for r in 1[1:]:
        if r > top: top = r
    return top
```

## **Debugging Programs**

#### **Debugging** = **Understanding** and **solving** errors

- ► The scientific method:
  - Study code and data to form hypotheses on origin of bug
  - Use repeatable experiments
- ► The tools:
  - Built-in Python editors and interpreters
  - Print statements to test hypotheses. Quickly locate bugs with prints at begin/end of functions (or use bisection)
  - **Systematic**: Make change, compare new vs. old, deduce, ...

```
1 = ['a','b','c'] >?
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
                     DS-GA 1007 | Lecture 2
```

```
1 = ['a', 'b', 'c']
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
                       DS-GA 1007 | Lecture 2
```

```
1 = ['a', 'b', 'c']
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
```

► IndexError: E.g., Trying to access beyond the limits of a list

▶ ?

DS-GA 1007 | Lecture 2

```
1 = ['a', 'b', 'c']
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
```

- ► IndexError: E.g., Trying to access beyond the limits of a list
- TypeError: E.g., Trying to convert an inappropriate type (list > int)

```
1 = ['a', 'b', 'c']
                         ► IndexError: E.g., Trying to access
                            beyond the limits of a list
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
```

```
1 = ['a','b','c']
1[3]
int(1)
1[2]/4
c/4
```

► IndexError: E.g., Trying to access beyond the limits of a list

TypeError: E.g., Trying to convert an inappropriate type, mixing inappropriate data types, etc

▶ ?

```
len(['a','b','c']
open('c.dat')
```

```
1 = ['a', 'b', 'c']
                          ► IndexError: E.g., Trying to access
                             beyond the limits of a list
1[3]
                          ► TypeError: E.g., Trying to convert
int(1)
                             an inappropriate type, mixing
1[2]/4
                             inappropriate data types, etc
                          ▶ NameError: E.g., Referencing a
c/4
                             non-existent variable
len(['a','b','c']
open('c.dat')
```

```
1 = ['a', 'b', 'c']
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
```

- ► IndexError: E.g., Trying to access beyond the limits of a list
- TypeError: E.g., Trying to convert an inappropriate type, mixing inappropriate data types, etc
- NameError: E.g., Referencing a non-existent variable
- SyntaxError: E.g., Forgetting to close parenthesis, quotation, etc
- ▶ ?

```
1 = ['a', 'b', 'c']
1[3]
int(1)
1[2]/4
c/4
len(['a','b','c']
open('c.dat')
```

- ► IndexError: E.g., Trying to access beyond the limits of a list
- TypeError: E.g., Trying to convert an inappropriate type, mixing inappropriate data types, etc
- NameError: E.g., Referencing a non-existent variable
- SyntaxError: E.g., Forgetting to close parenthesis, quotation, etc
- ► IOError: File not found

## **Pre-emptively Handling Errors**

#### **Exception Handlers**

*try/except/raise*: **Try** a block of code, if execution hits unexpected condition, handle this **except**ion with specific instructions, or **raise** an error which stops execution

#### **Example:**

```
def squareroot(x):
    try:
        return(math.sqrt(x))
    except ValueError:
        print("Warning: Input is not positive")
        return(math.sqrt(-x))
    except:
        raise TypeError("Stopped: Input is not a number")
```

# **Pre-emptively Handling Errors**

#### **Assertion Handlers**

**assert**: Stop execution and raise error if assumptions are not met. This pre-emptively locates sources of bugs as soon as introduced and avoid propagating them (*defensive programming*)

#### **Example:**

```
def ratio(x,y):
   assert y != 0,'Denominator of ratio is zero'
   return x/y
```

# Thank you!